MEXTECH ™

INSTRUMENTS OF TOMORROW

INTERNATIONAL ACCREDITED COMPANY BS EN ISO 9001:2008 — UKAS QUALITY MANAGEMENT Registration Number 046

Analog Clamp Meter M7150



Key Specifications/Special Features:

- AC voltage: 500V +/- 5% full scale
- AC current: 5/25/50A +/- 5% full scale
- Operating temperature: 0 deg.C up to 40 deg. C at RH < 80%
- No batteries are needed.

Analog Clamp Meter M7110



Key Specifications/Special Features:

- DC voltage: 60V +/- 3% full scale
- AC voltage: 150/300/600V +/- 4% full scale
- AC current: 6/15/60/150/300A +/- 3% full scale
- Resistance: 2K/200 K ohm +/-4% full arc
- Temperature: -20 to 150 degx C / 0 to 300 deg x F (5% full arc)
- Operating temperature: 0 deg. C up to 40 deg. C at RH < 80%
- Power supply: 1 x 1.5V, IEC LR6/AA
- IEC 61010, CAT II 600V

Analog Clamp Meter M7160



Key Specifications/Special Features:

- AC voltage: 300/600V +/- 5% full scale
- AC current: 3/12/60/300A +/-5% full scale
- Resistance: 2K/200 K ohm +/- 5% full arc
- Temperature: -20 to 150 deg. C / 0 to 300 deg. F (5% full arc)
- Operating temperature: 0 deg. C up to 40 deg. C at RH < 80%
- Power supply: 1 x 1.5V, IEC LR03/AAA
- IEC 61010, CAT II 300V.